



Repositionable Paper Label Material

7113 • 7142

Technical Data

January, 2007

Product Description

3M™ Repositionable Paper Label Material 7113 and 7142 with 3M™ Adhesive 1000 offer unique, one-piece removability from many surfaces, including fragile papers, and can be repositioned repeatedly for reuse on the same surface or application to another surface.

- 3M label material 7113 meets TAPPI #213 spec for repulpability.
- 3M label material 7142 is thermal transfer printable. Suggested ribbon inks include wax ribbons such as Sato Standard Wax and Iimak HighMark; wax/resin ribbons such as Zebra 5114, Sony Signature Series Hybrid, Dai Nippon M-230, Ricoh B110A and Sata Permier II; resin ribbons such as ICS C.C.4099-1, Sony 4041 and Astro-Med RF.

Construction

Product Number	Facestock	Adhesive	Liner
3M label material 7113	4.0 mil (102 microns) 46# uncoated litho paper	Not measurable – 1000 repositionable acrylic	3.2 mil (81 microns) 50# densified kraft
3M label material 7142	2.7 mil (69 microns) 55# semi-gloss paper	Not measurable – 1000 repositionable acrylic	2.5 mil (64 microns) 40# kraft glassine

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Conformability	Can conform to large diameter simple curved higher surface energy surfaces.
Printing	Flexographic, gravure
Temperature Range	-20°F (-20°C) to 250°F (121°C)
Minimum Application Temperature	5°F (-15°C)
Die-Cutting	Rotary or flatbed
Dispensing	Suitable for manual application

3M™ Repositionable Paper Label Material

7113 • 7142

Adhesion

Note: Peel test procedure is ASTM D-3330

	Initial (10 Minute Dwell/RT)		Conditioned for 3 Days at 120°F (49°C)*	
	180° Peel		180° Peel	
Surface	oz/in	N/100 mm	oz/in	N/100 mm
Stainless Steel	3.0	3.3	8.0	8.8
Bond Paper	2.0	2.2	2.0	2.2
Kraft Paper	1.0	1.1	1.0	1.1
Corrugated Board	1.0	1.1	1.0	1.1
Painted Metal	3.0	3.3	3.0	3.3
Glass	3.0	3.3	2.0	2.2
Polypropylene	3.0	3.3	2.5	2.7
Acrylic	5.0	5.5	3.0	3.3
Cellophane	2.5	2.7	2.0	2.2

*Adhesive shadow may occur

Liner Release

Note: Average 180° removal from facstock

90"/minute grams/1" width	300"/minute grams/1" width
20-50	70-150

Environmental Performance

Samples were applied to stainless steel panels and allowed to dwell for 24 hours prior to exposures.

Temperature Resistance:

175°F (79°C) for 1 day:

adhesive transfer may occur

-40°F (-40°C) to 200°F (93°C) for 1 day:

no change

Application Ideas

- These label materials can be used for point-of-purchase advertising labels and information labels for consumer appliances or electronics.
- 3M™ Repositionable Paper Label Material 7113 can be used for labels for identification and tracking within paper mills.
- 3M™ Repositionable Paper Label Material 7142 is designed for removal or repositionable labels that require variable information via thermal transfer printing such as auto window stickers with computer-generated information auto options, costs, and pricing.

3M™ Repositionable Paper Label Material

7113 • 7142

Application Techniques

- Not recommended for use on clay-coated papers or vinyl surfaces.
- Should be thoroughly evaluated for applications that utilize automatic hand-held applicators.
- Label size should be larger than 1" x 1" (2.54 cm x 2.54 cm).
- Silicone overspray/contamination of the substrate may cause poor adhesion.
- Packaging converted stock in low-density polyethylene (2-4 mils) can help prevent humidity penetration and stabilize the moisture content in the paper liners.
- Lower processing speeds may improve matrix removal – high nip or windup pressures can create a temporary or permanent increase in adhesion level.

Note: 3M™ Repositionable Paper Label Materials have a very low adhesion value on kraft paper and corrugated board.

Storage

Store at room temperature conditions of 72°F (22°C) and 50% relative humidity.

Shelf Life

If stored under proper conditions, product retains its performance and properties for two years from date of manufacture.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



**Industrial Business
Converter Markets
Industrial Adhesives and Tapes Division**

1030 Lake Road
Medina, OH 44256-0428
800-422-8116 • 877-722-5072 (fax)
www.3M.com/converter



*Recycled Paper
40% pre-consumer
10% post-consumer*

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2007 70-0709-4405-6 (1/07)